



Technical Data Sheet

Published on: 01/12/2010
Reviewed on: 17/07/2014

PRODUCT CODE:
ECS-NS60

Product Name :

ECWA - NS60

DESCRIPTION/APPLICATION etc.

DESCRIPTION:

ECWA-NS60: NONIONIC SURFACTANT BLEND of FATTY ALCOHOL POLYGLYCOL ETHER

FORMULATION/COMPOSITION:

- ECWA - NS60** is a Nonionic Surfactant blend of both Straight chain and Branched chain fatty alcohol hydrophobes.
- Composition:**
 - % Straight Chain Fatty Alcohol Ethoxylates : Proprietary
 - % Branched Chain Fatty Alcohol Ethoxylates : Proprietary

PROPERTIES/APPLICATIONS/USE :

- * **ECWA-NS60** is essentially designed as an **Environmentally Safe 0.7:1 Drop-In Replacement** for NP6 in most **General Cleaning and Degreasing Formulation** in order to cover the requirements for: **Dispersancy;Emulsification;Wetting;General Detergency; and Rinseability**
- * **ECWA-NS60** is Suitable/Compatible for use in the following Product Classes:
HI & I Cleaners/ Dishwashing Liquid and Degreasers / Hard Surface Cleaners / Agrochemicals Industrial Hand Cleaners & Hand-Soaps / Auto Care Products / Metal Cleaners /Dust Control/ Paper & Textile Processing / Paints & Coatings,Lubricants, Etc.
- * **ECWA - NS60** is Dispersable in Water
- * **ECWA - NS60** is Soluble in most Non Polar Solvents and Oils
- * **ECWA - NS60** is Chemically stable in the presence of Dilute Acids,Bases and Salts
- * **ECWA - NS60** is Compatible with Soaps,Anionic & other Nonionic Surfactants & most Polar Organic Solvents.
- * **ECWA - NS60** needs to be included at between 0.1% for ready-to-use type Spray-On Products up to 5-10% in Concentrated Products being diluted 50-100 times before Use.

SAFETY & HANDLING : Always consult the Material Safety Data Sheet before Use

Physical & Chemical properties

Physical state: LIQUID
Appearance:: Colourless/Clear/Turbid
Odour: TYPICAL
Specific Gravity (Density): : 0.89-1.00g/cm³ @ 20°C
Solubility.....: In OIL & most non Polar Solvents
pH - (20°C- 5% Aq.Sol): 8.00 - 9.00

Physical & Chemical properties - Continued

Cloud Point (5% Aq.Sol).....: Insoluble
Flash Point (Closed Cup,ASTM 93)... : 281°C
Colour (APHA): MAX 5
HLB.....: 10.90 ± 0.15
Dispersability: Dispersable in WATER
Degree of ETHOXYLATION: Proprietary Blend of Fatty Alcohol Ethoxyl.in short chain second.alcohol-70% Conc.

Disclaimer / Non-warranty

This product has been subjected to limited tests and has been shown to perform well. The information contained herein is to our best knowledge true and accurate, but since the conditions of use are beyond our control, Ecwamix Chemical Systems cc. disclaims any liability in connection with the use of this product and/or information. Warranty extends only as far as to the replacement of material shipped if not compliant with the specification as set out in the attached "Certificate of Analysis" and within the expiry period of the said product. All recommendations or suggestions are made without guarantee. It is good practice to conduct one's own application tests on a small area prior to using the product.

Ecwamix
Chemical Systems

3 Granville Ave, Lea Glen, Roodepoort
Gauteng, South Africa, 1709.
P.O.Box 6403, Westgate, Roodepoort
Gauteng, South Africa, 1734
Tel: +27 011 472-2256
Fax: +27 011 472-2121
E-mail: ecwamix@netactive.co.za
Web: www.ecwamix.co.za

Reg. No: CK2005/156636/23 VAT No: 4570227746



Technical Data Sheet

Published on: 01/12/2010
Reviewed on: 17/07/2014

PRODUCT CODE:
ECS-NS60

Product Name : **ECWA - NS60**

DESCRIPTION/APPLICATION etc.- CONTINUED

FORMULATION HINTS:

- * Where Thick Gel-like products are desired, we recommend the use of such techniques as the interplay between SLES,CDE,SULPHONIC ACID and SALT to achieve this, rather than to try thickening the products by using the Gel-Phase of a chosen surfactant, which in most cases are simply a waste of surfactant.
- * The inclusion of nonionic surfactants with an HLB similar to **ECWA - NS906/908** in a water-based formulation assists with good Wetting as well as Good Rinsing Off of all surfaces after the formulated product has performed it's Primary Function.For this reason, even if a formula is based largely on the use of Anionic Surfactants (SLES/SDDBSA/SLABS), it is always advisable to include even as little as 0.5% of **ECWA - NS906/908** in the cleaning formula, where the final dilution of the product is up to 20-50 times.Where products are largely based on high-alkalinity cleaning functionality, they often lose Rinseability, something that every user of a Cleaner/Degreaser-type product deploras, because a product can only clean to the level of how well one can Rinse it off after cleaning.
- * **ECWA - NS906/908** will not play a big role in the Rheology of a Formulation and will likewise only exhibit moderate abilities to Hydrotrope the inclusion of Salts.For high level of salts we recommend that a suitable hydrotrope be incorporated in order to stabilize your formula.

STORAGE/SHELF LIFE:

This product should be stored in it's original packaging(tightly sealed), indoors in ambient conditions, between 10°C - 38°C. Under these storage conditions,this product will be stable for up to 2 years.Thereafter test parameters should be confirmed before use.

PACKAGING: ECWA- NS60 is available in:	HLB Range:
20 Kg - HDPE BLOWPACK	1. < 10: W/O Emulsifier
180 Kg - HDPE BLOWPACK	2. > 10: O/W Emulsifier
950 Kg - IBC (FLOBIN)	3. 10 - 15: Good Wetting
	4. 12 - 15.....: Detergents

SAFETY & HANDLING : Always consult the Material Safety Data Sheet before Use

SPECIAL NOTES/CAUTIONS

- 1: Although **ECWA- NS60** is recommended as a Drop-In Replacement for NP6 used in formulations,due to the Proprietary nature of Specific/Special Formulations,this product should always be Tested for Useage Level/Suitability for Use within a formula before Batching-Up.
2. Due to **ECWA- NS60** being a blend, stir or agitate mildly after prolonged storage periods or inactivity and after having been exposed to extreme temperature fluctuations.

Disclaimer / Non-warranty

This product has been subjected to limited tests and has been shown to perform well. The information contained herein is to our best knowledge true and accurate, but since the conditions of use are beyond our control, Ecwamix Chemical Systems cc. disclaims any liability in connection with the use of this product and/or information. Warranty extends only as far as to the replacement of material shipped if not compliant with the specification as set out in the attached "Certificate of Analysis" and within the expiry period of the said product. All recommendations or suggestions are made without guarantee. It is good practice to conduct one's own application tests on a small area prior to using the product.

Ecwamix
Chemical Systems

3 Granville Ave, Lea Glen, Roodepoort
Gauteng, South Africa, 1709.
P.O.Box 6403, Westgate, Roodepoort
Gauteng, South Africa, 1734
Tel: +27 011 472-2256
Fax: +27 011 472-2121
E-mail: ecwamix@netactive.co.za
Web: www.ecwamix.co.za

Reg. No: CK2005/156636/23 VAT No: 4570227746